

Home > SSD > GIGABYTE M.2 PCIe SSD 128GB

# GIGABYTE

## M.2 PCIe

### SSD 128GB

Key Features Specification Support

Buy

 Where To Buy

News & Awards

 Online Store

GP-GSM2NE8128GNTD

Interface    PCI-Express 3.0 x2, NVMe 1.3

Form Factor    M.2 2280

Total Capacity    128GB

NAND    NAND Flash

External DDR Cache    N/A

Sequential Read speed    Up to 1100 MB/s

Sequential Write speed    Up to 500 MB/s

Random Read    Up to 90K

## IOPS

---

### Random Write IOPS

Up to 100K

---

### Dimension

80 x 22 x 2.3 mm

---

### Mean time between failure (MTBF)

1.5M hours

---

### Power Consump tion (Active)

Average : R : 2510mW ; W : 1850mW

---

### Power Consump tion (Idle)

50mW

---

### Temperat ure (Operatin g)

0°C to 70°C

---

### Temperat ure (Storage)

-40°C to 85°C

---

### Warranty

1. Limited 3-years or 100TBW.
2. Limited warranty based on 3 years or 100TBW, whichever comes first. (\*TBW is evaluated by JEDEC workload standard. )  
\*TBW (Terabyte Written): Terabytes Written is the total amount of data that can be written into a SSD before it is likely to fail.
3. When the usage of an NVME SSD as indicated by the "Percentage Used" (SMART ID:

05) in SMART page of "GIGABYTE SSD toolbox" reaches 100 means out of warranty. (A new unused product will show the number of 0)

Note

- Test system configuration: configuration may vary by models, we will choose the latest platform for verification.
- Performance may vary based on SSD's firmware version and system hardware & configuration. Sequential performance measurements based on CrystalDiskMark and IOmeter 1.1.0.
- Speeds based on internal testing. Actual performance may vary.
- 1GB = 1 billion bytes. Actual useable capacity may vary.

\* The entire materials provided herein are for reference only. GIGABYTE reserves the right to modify or revise the content at anytime without prior notice.

\* Advertised performance is based on maximum theoretical interface values from respective Chipset vendors or organization who defined the interface specification. Actual performance may vary by system configuration.

\* All trademarks and logos are the properties of their respective holders.

\* Due to standard PC architecture, a certain amount of memory is reserved for system usage and therefore the actual memory size is less than the stated amount.



Where To Buy



Online Store

DISCOVER

Join Us

Customer Care

COMPANY

About Us

CSR

News

CONSUMER

Motherboard

Graphics Card

Laptop

ENTERPRISE

Server Motherboard

Rack Server

GPU Server

SOLUTION

Application Solutions

Industry Solutions

SERVICE / SUPPORT

Consumer Products

Enterprise Products

7/5/24, 1:26

GIGABYTE M.2 PCIe SSD 128GB Specification | SSD - GIGABYTE U.S.A.

GIGABYTE Stable Models (GSM)  Business Center	Career	Monitor	High Density Server	RESOURCE	Online Support
	Investor	Desktop PC	Advanced Cooling	Insight	
	Contact Us	PC Peripherals	ARM Server	Success Case	
		PC Components	Storage Server	Awards	
			Edge Server	News	
			Tower Server / Workstation	Events	
			Embedded Computing		

FOLLOW US

