

Home > SSD > AORUS Gen4 7300 SSD 2TB

AORUS Gen4 7300 SSD 2TB

Key Features Specification Support

Buy

Where To Buy

Online Store

News & Awards Gallery

AG4732TB

Interface PCI-Express 4.0 x4, NVMe 1.4

Form Factor M.2 2280

Total Capacity 2000GB

NAND 3D TLC NAND Flash

External DDR Cache DDR4 2GB

Sequential Read speed Up to 7300 MB/s

Sequential Write speed Up to 6850 MB/s

Dimension SSD without Heatsink: 80 x 22 x 3.5 mm (Double Side)

SSD with Heatsink: 80.5 x 23.5 x 11.25 mm

Mean time between failure (MTBF)	1.6 million hours
Max. Operating Power	Read: 8.1W Write: 7.4W
Power Consumption (Idle, PS3)	30mW
Power Consumption(PS4, L1.2)	3mW
Temperature (Operating)	0°C to 70°C
Temperature (Storage)	-40°C to 85°C
Warranty	1. Limited 5-years or 1400TBW. 2. Limited warranty based on 5 years or 1400TBW, whichever comes first. (*TBW is evaluated by JEDEC workload standard.) *TBW (Terabyte Written): Terabytes Written is the total amount of data that can be written into a SSD before it is likely to fail. 3. When the usage of an NVME SSD as indicated by the "Percentage Used" (SMART ID: 05) in SMART page of "GIGABYTE SSD

toolbox" reaches 100 means out of warranty. (A new unused product will show the number of 0)

Note

- Test system configuration: configuration may vary by models, we will choose the latest platform for verification.
- Performance may vary based on SSD's firmware version and system hardware & configuration. Sequential performance measurements based on CrystalDiskMark and IOMeter 1.1.0.
- Speeds based on internal testing. Actual performance may vary.
- 1GB = 1 billion bytes. Actual useable capacity may vary.

Test Configuration

OS: Windows 11 22H2 (OS build 22621.819)
CPU: AMD Ryzen 9 7950X 16-Core Processor
4.5G
Memory: DDR5 5600 16GBx2
Chipset: AM5 X670 (X670E AORUS MASTER)

- * The entire materials provided herein are for reference only. GIGABYTE reserves the right to modify or revise the content at anytime without prior notice.
- * Advertised performance is based on maximum theoretical interface values from respective Chipset vendors or organization who defined the interface specification. Actual performance may vary by system configuration.
- * All trademarks and logos are the properties of their respective holders.
- * Due to standard PC architecture, a certain amount of memory is reserved for system usage and therefore the actual memory size is less than the stated amount.

Customer Care	CSR	Graphics Card	Rack Server	Industry Solutions	Enterprise Products
GIGABYTE Stable Models (GSM)	News	Laptop	GPU Server		Online Support
Business Center	Career	Monitor	High Density Server	RESOURCE	
	Investor	Desktop PC	Advanced Cooling	Insight	
	Contact Us	PC Peripherals	ARM Server	Success Case	
		PC Components	Storage Server	Awards	
			Edge Server	News	
			Tower Server / Workstation	Events	
			Embedded Computing		

FOLLOW US

