

Home > SSD > AORUS NVMe Gen4 SSD 1TB

AORUS NVMe Gen4 SSD 1TB

Key Features Specification Support

Buy
Where To Buy
Online Store

News & Awards Learn more

GP-ASM2NE6100TTTD

Interface PCI-Express 4.0x4, NVMe 1.3

Form Factor M.2 2280

Total Capacity 1000GB

NAND 3D TLC Toshiba BiCS4

External DDR Cache DDR4 1GB

Sequential Read speed Up to 5000 MB/s

Sequential Write speed Up to 4400 MB/s

Random Read up to 750k

IOPS

Random
Write
IOPS up to 700k

Dimension
 80.5 x 11.25 x 23.5 mm

Mean
time
between
failure
(MTBF) 1.77 million hours

Power
Consump
tion
(Active) Average: R : 6.6W; W : 6.4W

Power
Consump
tion (Idle) 18.8mw

Temperat
ure
(Operatin
g) 0°C to 70°C

Temperat
ure
(Storage) -40°C to 85°C

Warranty 1. Limited 5-years or 1800TBW.
 2. Limited warranty based on 5 years or
 1800TBW, whichever comes first. (*TBW is
 evaluated by JEDEC workload standard.)
 *TBW (Terabyte Written): Terabytes Written is
 the total amount of data that can be written into
 a SSD before it is likely to fail.
 3. When the usage of an NVME SSD as
 indicated by the "Percentage Used" (SMART ID:

05) in SMART page of "GIGABYTE SSD toolbox" reaches 100 means out of warranty. (A new unused product will show the number of 0)

Note

- Test system configuration: configuration may vary by models, we will choose the latest platform for verification.
- Performance may vary based on SSD's firmware version and system hardware & configuration. Sequential performance measurements based on CrystalDiskMark and IOmeter 1.1.0.
- Speeds based on internal testing. Actual performance may vary.
- 1GB = 1 billion bytes. Actual useable capacity may vary.

* The entire materials provided herein are for reference only. GIGABYTE reserves the right to modify or revise the content at anytime without prior notice.

* Advertised performance is based on maximum theoretical interface values from respective Chipset vendors or organization who defined the interface specification. Actual performance may vary by system configuration.

* All trademarks and logos are the properties of their respective holders.

* Due to standard PC architecture, a certain amount of memory is reserved for system usage and therefore the actual memory size is less than the stated amount.



Where To Buy



Online Store

DISCOVER	COMPANY	CONSUMER	ENTERPRISE	SOLUTION	SERVICE / SUPPORT
Join Us	About Us	Motherboard	Server Motherboard	Application Solutions	Consumer Products
Customer Care	CSR	Graphics Card	Rack Server	Industry Solutions	Enterprise Products
	News	Laptop	GPU Server		

GIGABYTE Stable Models (GSM) Business Center	Career	Monitor	High Density Server	RESOURCE	Online Support
	Investor	Desktop PC	Advanced Cooling	Insight	
	Contact Us	PC Peripherals	ARM Server	Success Case	
		PC Components	Storage Server	Awards	
			Edge Server	News	
			Tower Server / Workstation	Events	
			Embedded Computing		

FOLLOW US

