

Specifications

Interface	Sequential Read
PCIe Gen 4.0 x4, NVMe 2.0	Up to 7,450 MB/s * Performance may vary based on system hardware & configuration
Sequential Write	Warranty
Up to 6,900 MB/s * Performance may vary based on system hardware & configuration	5-Year Limited Warranty or 600 TBW Limited Warranty
Application	Weight
Client PCs, Game Consoles	Max 9.0g Weight

General Feature	Application	Capacity
	Client PCs, Game Consoles	1,000GB (1GB=1 Billion byte by IDE) be less (due to formatting, partitioning or otherwise)
	Form Factor	Interface
	M.2 (2280)	PCIe Gen 4.0 x4, NVMe 2.0
	Dimension (WxHxD)	Weight
	80 x 22 x 2.3 mm	Max 9.0g Weight
	Storage Memory	Controller
	Samsung V-NAND 3-bit MLC	Samsung in-house Controller
	Cache Memory	
	Samsung 1GB Low Power DDR4 SDRAM	

Special Feature	TRIM Support	S.M.A.R.T Support
	Supported	Supported
	GC (Garbage Collection)	Encryption Support
	Auto Garbage Collection Algorithm	AES 256-bit Encryption (Class 0)TCG drive)
	WWN Support	Device Sleep Mode Support
	Not supported	Yes

Performance	Sequential Read	Sequential Write
	Up to 7,450 MB/s * Performance may vary based on system hardware & configuration	Up to 6,900 MB/s * Performance may & configuration
	Random Read (4KB, QD32)	Random Write (4KB, QD32)
	Up to 1,200,000 IOPS * Performance may vary based on system hardware & configuration	Up to 1,550,000 IOPS * Performance hardware & configuration

<b>Random Read (4KB, QD1)</b> Up to 22,000 IOPS * Performance may vary based on system hardware & configuration	<b>Random Write (4KB, QD1)</b> Up to 80,000 IOPS * Performance may vary based on system hardware & configuration
--	---

Environment

<b>Average Power Consumption (system level)</b> *Average: 5.4 W*Maximum: 7.8 W (Burst mode)* Actual power consumption may vary depending on system hardware & configuration	<b>Power consumption (Idle)</b> Max. 50 mW * Actual power consumption may vary depending on system hardware & configuration
<b>Allowable Voltage</b> 3.3 V ± 5 % Allowable voltage	<b>Reliability (MTBF)</b> 1.5 Million Hours Reliability (MTBF)
<b>Operating Temperature</b> 0 - 70 °C Operating Temperature	<b>Shock</b> 1,500 G & 0.5 ms (Half sine)

Accessories

<b>Installation Kit</b> Not Available
--

Software

<b>Management SW</b> Magician Software for SSD management
--

Warranty

5-Year Limited Warranty or 600 TBW Limited Warranty
---